




Serie / series / série: **PRO-FL**



0.5	0.96 0.96	E07 E(C)20 E(C)0	4036 877 868
1.0	1.91 1.92	E07 E(C)20 E(C)0	1159 219 217
1.5	2.87 2.89	E07 E(C)20 E(C)0	515 97 96
2.0	3.82 3.85	E07 E(C)20 E(C)0	290 55 54
2.5	4.78 4.81	E07 E(C)20 E(C)0	185 35 35
3.0	5.73 5.77	E07 E(C)20 E(C)0	129 24 24

— C0 = 1180 (81.8°)
— C0 = 2270 (80.4°)

Ref. **01181-XXXX**

	- 0	- 1	- 2
* Colores:	blanco	negro	gris
* Colours:	white	black	grey
* Couleurs:	blanc	noir	gris
* Temp. color/colour/couleur:	- G 827*	- C 830	- N 840
		- H 927*	
* Ángulo / Angle / Angle:		- 8 80°	
* Lámpara / lamp / lampe:		- 3 2000LM 18W	
* Reg. corte fase / Dimmable by edge cut / Reggale per coupe phase :		- D	

Difusor opal incluido / Opale diffuser enclosed. / Difusor opal inclus

DESCRIPCIÓN | DESCRIPTION | DESCRIPTION

Downlights para LED Downlight de policarbonato con reflector de aluminio alta pureza.

LED downlights Policarbonato downlight with an aluminium reflector of high purity.

Downlights à LED. Downlight en policarbonato avec un réflecteur en aluminium d'haute pureté.


INSTALACIÓN | INSTALLATION | INSTALLATION

Empotrable 220 mm.

Embedding 220 mm.

Encastrement 220 mm.

CARACTERÍSTICAS TÉCNICAS | TECHNICAL FEATURES | CARACTÉRISTIQUES TECHNIQUES



CERTIFICADOS DE CALIDAD | QUALITY CERTIFICATE | CERTIFICAT DE QUALITÉ



FECHA DE ACTUALIZACIÓN / UPDATED ON:
DATE D'ACTUALISATION: **21-07-2016**

Tel: +34 937 154 712
Fax: +34 937 154 713
www.nexia.es
www.facebook.com/nexialighting
www.twitter.com/nexialighting