



Serie / series / série: **PRO-FL**



∅ 234mm



Beam Angle (°)	Beam Diameter (mm)	Illuminance (lx)	Beam Area (m²)	Beam Volume (m³)
160	160	0.56	0.02	0.0002
160	240	1.91	0.04	0.0004
160	320	2.87	0.08	0.0008
160	400	3.82	0.12	0.0012
160	480	4.78	0.18	0.0018
160	560	5.73	0.24	0.0024

CO - C180 (81.8°)  
C90 - C270 (80.4°)

3 años de garantía  
3 year warranty  
3 ans de garantie

Ref. **01183-XXXX**

	- 0	- 1	- 2
* Colores:	blanco	negro	gris
* Colours:	white	black	grey
* Couleurs:	blanc	noir	gris
* Temp. color/colour/couleur:		- C 830	- N 840
* Ángulo / Angle / Angle:		- 8 80°	
* Lámpara / lamp / lampe:		- 3 2000LM 18W	

\* Reg. corte fase / Dimmable by edge cut / Reggale per coupe phase : - R

Difusor opal incluido / Opale diffuser enclosed. / Difusor opal inclus  
IP54

**DESCRIPCIÓN | DESCRIPTION | DESCRIPTION**

Downlights para LED Downlight de policarbonato con reflector de aluminio alta pureza.

LED downlights Polycarbonate downlight with an aluminium reflector of high purity.

Downlights à LED. Downlight en policarbonate avec un réflecteur en aluminium d'haute pureté.

**INSTALACIÓN | INSTALLATION | INSTALLATION**

Empotrable 220 mm.

Embedding 220 mm.

Encastrement 220 mm.

**CARACTERÍSTICAS TÉCNICAS | TECHNICAL FEATURES | CARACTÉRISTIQUES TECHNIQUES**

210mm 650g 54 IP DRIVER CRI=80 / UGR<19 850° 230V

**CERTIFICADOS DE CALIDAD | QUALITY CERTIFICATE | CERTIFICAT DE QUALITÉ**



FECHA DE ACTUALIZACIÓN / UPDATED ON:  
DATE D'ACTUALISATION: 01-03-2016

Tel: +34 937 154 712  
Fax: +34 937 154 713  
www.nexia.es  
www.facebook.com/nexialighting  
www.twitter.com/nexialighting