



Serie / series / série: **PRO-FL**



∅ 234mm



Beam diameter (mm)	Beam diameter (in)	Beam diameter (ft)	Beam diameter (m)	Beam diameter (cm)	Beam diameter (mm)	Beam diameter (in)	Beam diameter (ft)	Beam diameter (m)	Beam diameter (cm)
0.5	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96	0.96
1.0	1.91	1.92	1.92	1.92	1.92	1.92	1.92	1.92	1.92
1.5	2.87	2.89	2.89	2.89	2.89	2.89	2.89	2.89	2.89
2.0	3.82	3.85	3.85	3.85	3.85	3.85	3.85	3.85	3.85
2.5	4.78	4.81	4.81	4.81	4.81	4.81	4.81	4.81	4.81
3.0	5.73	5.77	5.77	5.77	5.77	5.77	5.77	5.77	5.77

3 años de garantía
3 year warranty
3 ans de garantie

Tel: +34 937 154 712
Fax: +34 937 154 713
www.nexia.es
www.facebook.com/nexialighting
www.twitter.com/nexialighting

Ref. **01185-XXXX**

	- 0	- 1	- 2
* Colores:	blanco	negro	gris
* Colours:	white	black	grey
* Couleurs:	blanc	noir	gris
* Temp. color/colour/couleur:		- C 830	- N 840
* Ángulo / Angle / Angle:		- 8 80°	
* Lámpara / lamp / lampe:		- 3 2000LM 21W	
* Reg. corte fase / Dimmable by edge cut / Reggable per coupe phase :			- R

Difusor opal incluido / Opale diffuser enclosed. / Difusor opal inclus

DESCRIPCIÓN | DESCRIPTION | DESCRIPTION

Downlights para LED Downlight de policarbonato con reflector de aluminio alta pureza.

LED downlights Polycarbonate downlight with an aluminium reflector of high purity.

Downlights à LED. Downlight en policarbonate avec un réflecteur en aluminium d'haute pureté.

INSTALACIÓN | INSTALLATION | INSTALLATION

Empotrable 220 mm.

Embedding 220 mm.

Encastrement 220 mm.

CARACTERÍSTICAS TÉCNICAS | TECHNICAL FEATURES | CARACTÉRISTIQUES TECHNIQUES

210mm 650g 44 IP DRIVER CRI=80 / UGR<19 850° 230V

CERTIFICADOS DE CALIDAD | QUALITY CERTIFICATE | CERTIFICAT DE QUALITÉ



FECHA DE ACTUALIZACIÓN / UPDATED ON:
DATE D'ACTUALISATION: **01-03-2016**