



Serie / series / série: **PRO**



200x200mm

70mm



Altura (mm)	Ø (mm)	Iluminancia (lx)	Flujo luminoso (lm)
0.5	0.56	433	186
1.0	1.11	43.3	186
1.5	1.67	18.9	186
2.0	2.22	10.9	186
2.5	2.78	6.7	186
3.0	3.33	4.1	186

Ref. **01681-XXXX**

	- 0	- 1	- 2
* Colores:	blanco	negro	gris
* Colours:	white	black	grey
* Couleurs:	blanc	noir	gris
* Temp. color/colour/couleur:		- C 830	- N 840
* Ángulo / Angle / Angle:		- 8 80°	
* Lámpara / lamp / lampe:		- 3 2000LM 17W	
* Reg. corte fase / Dimmable by edge cut / Reggable per coupe phase :			- R

Difusor opal incluido / Opale diffuser enclosed. / Difusor opal inclus

DESCRIPCIÓN | DESCRIPTION | DESCRIPTION

Downlights para LED Downlight de policarbonato con reflector de aluminio alta pureza.

LED downlights Policarbonate downlight with an aluminium reflector of high purity.

Downlights à LED. Downlight en policarbonate avec un réflecteur en aluminium d'haute pureté.

INSTALACIÓN | INSTALLATION | INSTALLATION

Empotrable 185 mm.

Embedding 185 mm.

Encastrement 185 mm.

CARACTERÍSTICAS TÉCNICAS | TECHNICAL FEATURES | CARACTÉRISTIQUES TECHNIQUES

185x185mm 1500g 44 IP DRIVER CRI=80 / UGR<19 850°

CERTIFICADOS DE CALIDAD | QUALITY CERTIFICATE | CERTIFICAT DE QUALITÉ



FECHA DE ACTUALIZACIÓN / UPDATED ON: 28/02/2015
DATE D'ACTUALISATION:

Tel: +34 937 154 712
Fax: +34 937 154 713
www.nexia.es
www.facebook.com/nexialighting
www.twitter.com/nexialighting